



STANDARD FEATURES

- Rear-mount frame
- For openings in 1/2" (12.7 mm) or 5/8" (15.9 mm) drywall walls and ceiling
- Concealed aluminum frame, hardware and mechanical touch latch
- Factory installed moisture/ mold resistant drywall inlay
- Frame acts as finishing bead
- 1/16" perimeter gap
- Virtually invisible finishing
- Air tight with EPDM rubber perimeter gasket
- Superior acoustics with air tight seal and mass of drywall inlay
- Fully removable door leaf
- Free-pivot hinge and safety cable

Standard Sizes

(Custom sizes available upon request)

| Access Panel Size/ Clear Opening | | Weight | |
|-------------------------------------|-------------|----------|----------|
| Inch | mm | lbs-1/2" | lbs-5/8" |
| 6 x 6" | 152 x 152mm | 1.9 | 2.1 |
| 8 x 8" | 203 x 203mm | 2.4 | 2.8 |
| 10 x 10" | 254 x 254mm | 3 | 3.7 |
| 12 x 12" | 305 x 305mm | 3.7 | 4.6 |
| 14 x 14" | 356 x 356mm | 4.4 | 5.7 |
| 16 x 16" | 406 x 406mm | 5.2 | 6.9 |
| 18 x 18" | 457 x 457mm | 6.1 | 8.2 |
| 20 x 20" | 508 x 508mm | 7.1 | 9.7 |
| 24 x 24" | 610 x 610mm | 9.3 | 12.8 |
| 24 x 36" | 610 x 914mm | 12.7 | 18.1 |

BUY DIRECT from BAUCO for best pricing and shortest lead time.

Size

_____ " Width(X) x _____ " Length(Y)

Thickness

- 1/2"
 5/8"

Application

- Wall
 Ceiling

Latch Options

- (Standard) Mechanical Touch Latch
 Slotted Cam
 Torx Cam
 Keyed Lock

Inlay Options

- (Standard) Drywall
 Acoustic Board
 Plywood
 Tile Backer Drywall
 Plaster Board (to bond with plaster veneer)
 Double Layer

Time Saving Option

- Paint-ready Finish

Project: _____

Client: _____

Approved by: _____

Date: _____



1.877.592.0033 | info@bauco.com | bauco.com
834 Devonshire Road Victoria, BC, Canada V9A 4T4